

Tri-Deck Roller Mower

Winged, Trailed

The MAJOR TDR wide area mower is a multipurpose low-maintenance trailed rotary mower, designed to manage parklands, sports pitches and semi-rough golf course grass.

The three-point pivot frame allows the three decks to glide over the ground contours to achieve a perfect finish without scalping. The MAJOR TDR is available in 4.9m and 6.1m working widths.

The cutting rotors are fitted with two 5mm blades of optimum hardness and strength. The blades are designed to lift the grass and hold it inside the cutting chamber allowing the material to be chopped finely.

The blades are synchronised to rotate in opposite directions and overlap each other by 75mm. This overlap, in combination with high blade tip speeds ensures that all vegetation is finely cut and evenly dispersed to leave a professional striped finish equivalent to that of a cylinder mower.



Take a 360° virtual tour



The gear-driven drive line delivers consistent cutting rates, even in heavy and wet conditions.

The wings fold neatly to give a 2.5m transport width for safe transportation on public highways.

The MAJOR TDR is produced from high-performance Strenx™ 700 MC structural steel. This material is stronger yet lighter than conventional mild steel. This results in reduced soil compaction and lower fuel costs without compromising the strength of the machine. The machine is galvanised for the ultimate protection against corrosion, to safeguard your investment.



“



Watch Video

Our Major TDR16000 can cut through grass 6' high and then I can take 10 minutes to adjust the sets and go and cut a football pitch or a cricket out field. To do that with a cylinder mower is impossible. It is running constantly at max power for 7 hours a day and it just doesn't miss a beat."

Tasos Lambrou - Tractor Operator, Blackpool Council, UK

FEATURES

- The cutting height can be adjusted from 10mm – 140mm for year-round mowing
- Premium quality components - Walterscheid wide angle PTO drive shaft
- Sealed internal roller bearings give protection against moisture and soil. Easy maintenance and replacement
- The rear deck can be removed and used independently of the wings. Wings can be operated independently
- Braked axle and LED road lighting kit for ensures safe transportation when using public highways.
- BKT 300/65X12 turf tyres
- Remote control unit allows operation of the unit, at the touch of a button, from the tractor cab.
- Covered by a comprehensive three-year warranty



MODEL	MJTDR-490	MJTDR-610
Working Width	4.90m (15' 11")	6.10m (19' 11 ½")
Transport Width	2.57m (8' 5")	2.57m (8' 5")
Power (HP)	65 - 100	75 - 120
PTO rpm	540	540
Cutting Height	10 -140mm	10 -140mm
Rotors	8	10
Blades	16	20
Weight	2335kg	2550kg
Blade tip speed	76 m/s	76 m/s
Mowing Rates (Acres/hr at 7mph)	12 .15	15.23